

**Polyethylene slip tape, Width×length (mm× m): 19X16****Order data**

Order number	083790 19X16
GTIN	212001199106
Item class	08M

Description**Version:**

The **3M™ 5423** protects surfaces by virtue of its excellent resistance to abrasion. It creates a smooth surface which permits frictionless contact. There is no need for additional lubricants, which can so often be the source of problems. In addition it is **resistant to chemicals, transparent**, and with its protective paper it performs well in press tool processes.

Note:

The specified "best before" date for 3M™ products is in relation to compliance with the specified storage guidelines.

Technical description

Colour	transparent
Width	19.05 mm
Length	16.45 m
Thickness	0.28 mm
Manufacturer's designation	5423

Storage temperature	20 °C
Special features	abrasion resistant
Special features	self-lubricating
Special features	sliding
Tensile strength	9.63 N/mm
"Best before" date	12 mo
Type of adhesive tape	single-sided
Adhesive	Vulcanised rubber
Stretch capability	500 %
Backing material	PE film
Application	Abrasion protection
Application	Transport tracks and sliding tracks
Adhesive strength on steel	0.28 N/mm
Storage humidity	50 %
Liner present	no
temperature-resistant up to	-35 - 110 °C
Type of product	Adhesive tape