



Precision dial indicator IP54, shock-resistant, Measuring range / Body Ø: 10/58mm



Order data

Order number	432220 10/58
GTIN	2050001040206
Item class	43A

Description

Version:

Dial indicators with protection **against splashed water, oil and dirt**. Contact point on plunger spindle sealed by rubber bellows, sealed by protective sleeve at the top. Back wall sealed, glass and outer ring tightly screwed. Clamping shank \varnothing 8 mm h6.

Function:

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

Optional extras:

Special contact points No. 434900; 434910; 434915.

Technical description

Gauging force	0.7 - 1.6 N
Reading per pointer revolution	1 mm
Graduation	0.01 mm
Clamping shank \varnothing h6	8 mm

Body Ø	58 mm
Measuring range	10 mm
Calibration	C1
Standard	DIN 878
IP Index of Protection	IP 54
Measurement variation MPE (measurement range)	15 µm
Measurement technology	analogue
Packaging	sturdy box
Type of product	dial gauge

Services

CalibrationDial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 10 mm	023000 10
DAkkS calibrationDial indicator analogue 0.01 and digital 0.01 / 0.001 maximum measuring span 12,5 mm	023010 12,5

Accessories

Carbide contact point Type 10	434910 10
Steel contact point Type 11/35	434900 11/35
Steel contact point Type 18/4	434900 18/4
Steel contact point Type 32	434900 32
Steel contact point Type 12	434900 12
Steel contact point Type 14/15	434900 14/15
Steel contact point Type 16	434900 16
Carbide contact point Type 18/5	434910 18/5
Steel contact point Type 18/5	434900 18/5
Steel contact point Type 14	434900 14
Steel contact point Type 14/40	434900 14/40
Carbide contact point Type 14	434910 14

Carbide contact point Type 17	434910 17
Steel contact point Type 18/3	434900 18/3
Steel contact point Type 29/10	434900 29/10
Carbide contact point Type 18/2	434910 18/2
Steel contact point Type 19/9	434900 19/9
Steel contact point Type 39	434900 39
Steel contact point Type 40/7,8	434900 40/7,8
Carbide contact point Type 18/6	434910 18/6
Steel contact point Type 11	434900 11
Steel contact point Type 11/20	434900 11/20
Steel contact point Type 18/1	434900 18/1
Steel contact point Type 28	434900 28
Carbide contact point Type 11	434910 11
Steel contact point Type 13	434900 13
Carbide contact point Type 16	434910 16
Steel contact point Type 24	434900 24
Steel contact point Type 10	434900 10
Ruby contact point Type 2	434915 2
Carbide contact point Type 18/4	434910 18/4
Steel contact point Type 18/6	434900 18/6
Steel contact point Type 40/10	434900 40/10
Steel contact point Type 18/2	434900 18/2
Steel contact point Type 17	434900 17
Steel contact point Type 2	434900 2
Steel contact point Type 11/15	434900 11/15
Steel contact point Type 19/10	434900 19/10
Steel contact point Type 15	434900 15
Steel contact point Type 14/20	434900 14/20
Steel contact point Type 19/11	434900 19/11

Steel contact point Type 19/7	434900 19/7
Carbide contact point Type 18/3	434910 18/3
Steel contact point Type 11/30	434900 11/30
Carbide contact point Type 2	434910 2
Steel contact point Type 30/10	434900 30/10
Steel contact point Type 20	434900 20
Carbide contact point Type 18/1	434910 18/1
Steel contact point Type 14/30	434900 14/30
Steel contact point Type 11/25	434900 11/25
Steel contact point Type 29/20	434900 29/20
Steel contact point Type 19/8	434900 19/8