




Micrometer with dial comparator, Measuring range: 0-25mm



Order data

Order number	422501 0-25
GTIN	
Item class	46P

Description

Version:

Measuring spindle through hardened and ground.
 With precision lapped **carbide tipped anvils**.
 Spindle and anvil of stainless steel.
 One piece frame and spindle guide.
 Button for retracting the measurement anvil for repetitive measurements.
 With adjustment screw for zeroing.
 Tolerance pointers for good/ reject measurements.
 With hand temperature protection. Lever for spindle clamping.

Callout:

Deviation read-off in 1/1000 mm.
 Push button for anvil retraction.

Accuracy:

Dial comparator 1 µm – micrometer 2 µm.

Supplied with:

Adjustment wrench.

Note:

Measuring faces of CBN on request.

Technical description

Measuring range	0 - 25 mm
Graduation of the precision dial comparator	0.001 mm

Measuring range dial comparator	±0.07 mm
Graduation of the micrometer	0.01 mm
Clearance depth of micrometer frame	15 mm
Standard	DIN 863
Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B9
Type of product	Micrometer with dial comparator

Services

CalibrationIndicator micrometer maximum measuring range 25 mm	022100 25
---	-----------