

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 7,6mm



Order data

Order number	123025 7,6		
GTIN	4045197844033		
Item class	11E		

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- · Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.

A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Versions HB and HE supplied at the same price as HA.

Form **HB:** order with **No. 123026**.

Form **HE:** order with **No. 123025 + 129100HE**.

Technical description

Feed f in steel < 1100 N/mm ²	0.15 mm/rev.		
Shank Ø D _s	8 mm		
Standard	Manufacturer's standard		
Flute length L_c	76 mm		
Tolerance nominal Ø	h7		
Overall length L	114 mm		

Nominal ∅ D _c	7.6 mm		
recommended maximum drilling depth L_2	64.6 mm		
Number of cutting edges Z	2		
Series	Master Steel		
Coating	TiAIN		
Tool material	Solid carbide		
Version	8×D		
Point angle	135 degrees		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	green		
Type of product	Jobber drill		

User data

	Suitability	V _c	ISO code
Steel < 500 N/mm ²	suitable	195 m/min	Р
Steel < 750 N/mm ²	suitable	150 m/min	Р
Steel < 900 N/mm ²	suitable	135 m/min	Р
Steel < 1100 N/mm ²	suitable	125 m/min	Р
Steel < 1400 N/mm ²	suitable	80 m/min	Р
INOX < 900 N/mm ²	suitable only under restricted conditions	65 m/min	М
GG	suitable	120 m/min	K
GGG	suitable	115 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		



Services

Shank grinding Type HE 129100 HE