

# GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 13,8mm



### **Order data**

Order number	123025 13,8		
GTIN	4045197844545		
Item class	11E		

## **Description**

#### **Version:**

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- · Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.

A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

#### **Note:**

Flute length  $L_C = L_2 + 1.5 \times D_C$ .

Versions HB and HE supplied at the same price as HA.

Form **HB:** order with **No. 123026**.

Form **HE:** order with **No. 123025 + 129100HE**.

# **Technical description**

Overall length L	178 mm		
Flute length L <sub>c</sub>	133 mm		
Number of cutting edges Z	2		
Shank Ø D <sub>s</sub>	14 mm		
Nominal Ø D <sub>c</sub>	13.8 mm		
Feed f in steel < 1100 N/mm <sup>2</sup>	0.23 mm/rev.		



Tolerance nominal Ø	h7	
Standard	Manufacturer's standard	
recommended maximum drilling depth $L_2$	112.3 mm	
Series	Master Steel	
Coating	TiAlN	
Tool material	Solid carbide	
Version	8×D	
Point angle	135 degrees	
Shank	DIN 6535 HA to h6	
Through-coolant	yes, with 25 bar	
Machining strategy	HPC	
Semi-Standard	yes	
Colour ring	green	
Type of product	Jobber drill	

# **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Steel < 500 N/mm <sup>2</sup>	suitable	195 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	150 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	135 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	125 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	80 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	65 m/min	М
GG	suitable	120 m/min	K
GGG	suitable	115 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		



# **Services**

Shank grinding Type HE 129100 HE