## Garant

## GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 10,2mm

and the second second

## Order data

Order number	123025 10,2		
GTIN	4045197844293		
Item class	11E		

## Description

#### Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- $\cdot\,$  Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.

· Polished flutes for good chip clearance.

A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ . Versions HB and HE supplied at the same price as HA. Form **HB:** order with **No. 123026**. Form **HE:** order with **No. 123025 + 129100HE**.

## **Technical description**

Shank Ø D <sub>s</sub>	12 mm		
Feed f in steel < 1100 N/mm <sup>2</sup>	0.2 mm/rev.		
Number of cutting edges Z	2		
Overall length L	162 mm		
Nominal Ø D <sub>c</sub>	10.2 mm		
Standard	Manufacturer's standard		

recommended maximum drilling depth $L_2$	98.7 mm		
Flute length $L_c$	114 mm		
Tolerance nominal Ø	h7		
Series	Master Steel		
Coating	TiAIN		
Tool material	Solid carbide		
Version	8×D		
Point angle	135 degrees		
Shank	DIN 6535 HA to h6		
Through-coolant	yes, with 25 bar		
Machining strategy	HPC		
Semi-Standard	yes		
Colour ring	green		
Type of product	Jobber drill		

# User data

	Suitability	V <sub>c</sub>	ISO code
Steel < 500 N/mm <sup>2</sup>	suitable	195 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	150 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	135 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	125 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	80 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	65 m/min	М
GG	suitable	120 m/min	К
GGG	suitable	115 m/min	К
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		

© Hoffmann GmbH Qualitätswerkzeuge

# Services

Shank grinding Type HE

129100 HE