Garant

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7: 11,9mm

and the second

Order data

| Order number | 123225 11,9 |
|--------------|---------------|
| GTIN | 4045197845689 |
| Item class | 11E |

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- $\cdot\,$ Clear reduction in cutting forces due to special cutter geometry.
- · Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.
- A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068 – 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form HB: with No. 123226.

Order form **HE:** with **No. 123225 + 129100HE**.

Technical description

| Overall length L | 204 mm |
|--|----------|
| Number of cutting edges Z | 2 |
| Flute length L_c | 156 mm |
| recommended maximum drilling depth L_2 | 138.2 mm |
| Nominal Ø D _c | 11.9 mm |

| Shank Ø Ds | 12 mm | |
|--|-------------------------------|--|
| Standard | Manufacturer's standard | |
| Feed f in steel < 1100 N/mm ² | N/mm ² 0.2 mm/rev. | |
| Tolerance nominal Ø | h7 | |
| Series | Master Steel | |
| Coating | TiAIN | |
| Tool material | Solid carbide | |
| Version | 12×D | |
| Point angle | 135 degrees | |
| Shank | DIN 6535 HA to h6 | |
| Through-coolant | yes, to 25 bar | |
| Machining strategy | HPC | |
| Semi-Standard | yes | |
| Colour ring | green | |
| Type of product | Jobber drill | |

User data

| | Suitability | Vc | ISO code |
|--------------------------------|---|-----------|----------|
| Steel < 500 N/mm ² | suitable | 160 m/min | Р |
| Steel < 750 N/mm ² | suitable | 125 m/min | Р |
| Steel < 900 N/mm ² | suitable | 115 m/min | Р |
| Steel < 1100 N/mm ² | suitable | 105 m/min | Р |
| Steel < 1400 N/mm ² | suitable | 65 m/min | Р |
| INOX < 900 N/mm ² | suitable only under restricted conditions | 55 m/min | М |
| GG | suitable | 100 m/min | К |
| GGG | suitable | 95 m/min | К |
| Uni | suitable | | |
| wet maximum | suitable | | |

© Hoffmann GmbH Qualitätswerkzeuge

| wet minimum Services | suitable | |
|-------------------------|----------|-----------|
| Services | | |
| Shank grinding Type HE | | 129100 HE |