Garant

Solid carbide NC machine reamer Configurable, TiAlN, Nominal ∅ DC: 18mm

Order data

Order number	164344 18
GTIN	4045197857743
Item class	10N

Description

Version:
Version suitable for NC DIN 8093-2 **with straight shank** ∅ for **standard chucking** especially in **hydraulic chucks** or **high precision collet chucks.** This ensures **very high concentricity** and **process reliability**,
The use of GARANT-NC reamers eliminates the need to procure special collets. With long flutes and left-hand helix.
Reamers finish ground to match your specification.
Application:
For reaming through holes, as the chips are evacuated in the cutting direction. Lead taper is suitable also for blind holes.
Note:
For H7 fit see No. 164340 and 164341.

Technical description

Overhang L_1	132 mm
Number of cutting edges Z	8
Feed f in steel < 1100 N/mm^2	0.2 mm/rev.
∅ range	17.21 - 18.2 mm
Nominal ∅ D_C	18 mm
Shank ∅ D_s	18 mm
Shank tolerance	h6
Flute length L_c	52 mm

Overall length L	182 mm
Reaming oversize in diameter	0.2 - 0.3 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 8093
Through-coolant	no
Shank	DIN 6535 HA to h6
Application for type of drilling	for through hole
Colour ring	green
Type of product	Phillips bit

User data

	Suitability	V_c	ISO code
Aluminium	suitable	35 m/min	N
Aluminium (short chipping)	suitable	30 m/min	N
Alu > 10% Si	suitable only under restricted conditions	25 m/min	N
Steel < 500 N/mm²	suitable	30 m/min	P
Steel < 750 N/mm²	suitable	25 m/min	P
Steel < 900 N/mm²	suitable	20 m/min	P
Steel < 1100 N/mm²	suitable	15 m/min	P
Steel < 1400 N/mm²	suitable	10 m/min	P
INOX < 900 N/mm²	suitable	15 m/min	M
INOX > 900 N/mm²	suitable	12 m/min	M
Ti > 850 N/mm²	suitable only under restricted conditions	10 m/min	S
GG(G)	suitable	10 m/min	K
CuZn	suitable	25 m/min	N
Uni	suitable		

wet maximum	suitable