



## Flap disc (special ZA) glass fibre pad flat, 115 mm Ø, Grit: 36

### Order data

|              |               |
|--------------|---------------|
| Order number | 565300 36     |
| GTIN         | 4045197230300 |
| Item class   | 51M           |

### Description

#### Version:

Roughing grinding discs with cloth flaps coating with Zirconium Aluminium Oxide (ZA) or ceramic grit on backing pads of steel, plastic or glass fibre. Circumferential speed **ideally 50-60 m/s**, max. 80 m/s. Gentle, cool grinding with high self-sharpening effect (no clogging); low vibration and low force working, low noise level.

· **Flat shape – for surface grinding – and weld dressing with approach angles 0 -15°.**

Flap disc with glass fibre pad and polyester fabric with greatly above-average working life.

**Exceptional metal removal rate.**

#### Application:

Universal for **all steels**, even for use on **hardened edges**.

Grinding medium code: ZA

Iron, sulphur and chlorine constituents: < 0.1 %

optimised for material: Steel

optimised for material: INOX

maximum circumferential speed: 80 m/s

Shape description: flat

Bore Ø: 22.23 mm

### Technical description

|                                   |         |
|-----------------------------------|---------|
| Backing pad                       |         |
| Bonding                           |         |
| maximum circumferential speed     | 80 m/s  |
| recommended circumferential speed | m/s     |
| Grit structure                    |         |
| recommended approach angle        | degrees |

|   |          |
|---|----------|
| Grinding media                          |          |
| Grinding medium code                    | ZA       |
| Adapter                                 |          |
| optimised for material                  | Steel    |
| optimised for material                  | INOX     |
| Iron, sulphur and chlorine constituents | < 0.1 %  |
| See-through grinding                    |          |
| Shape                                   |          |
| suitable for quick-change system        |          |
| abrasive, cooling coating               |          |
| Grinding media backing                  |          |
| Propulsive equipment                    |          |
| Thread                                  |          |
| Product name attribute                  | 115 mm Ø |
| maximum speed                           | rpm      |
| Type of product                         |          |