

HOLEX®
Coarse cleaning disc (SiC), 76.2 mm Ø, Fleece version: CRS

Order data

Order number	554039 CRS
GTIN	4045197525901
Item class	52E

Description
Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing "with a single twist of the wrist" in a very short time.

Coarse cleaning disc with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad. Open structure, will not clog. **High material removal rate** for general-purpose cleaning work.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

For rust removal, paint removal, dressing weld seams and removing surface dirt.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Grinding medium code: SiC

Iron, sulphur and chlorine constituents: < 0.1 %

Grit designation: extra coarse

Degree of hardness: hard

maximum speed: 15000 rpm

Technical description

maximum speed	15000 rpm
---------------	-----------

Grit designation	extra coarse
Degree of hardness	hard
Disc Ø	76.2 mm
Grinding media	Silicon carbide (SiC)
Grinding medium code	SiC
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	76.2 mm Ø

Accessories

Rubber backing pad shank Ø 6 mm. hard External Ø 75 mm	554089 75
Rubber backing pad shank Ø 6 mm. medium External Ø 75 mm	554092 75
Rubber backing pad shank Ø 6 mm. medium hard External Ø 75 mm	554093 75
Rubber backing pad with M14 mounting hard External Ø 75 mm	554094 75
Rubber backing pad with mounting M14 hard External Ø 75 mm	554088 75
Rubber backing pad shank Ø 6 mm. soft External Ø 75 mm	554091 75
Plastic backing pad shank 6 mm Ø External Ø 75 mm	554090 75