

3M Roloc™**Fleece disc GB-DR, Ø 76.2 mm, Grit equivalent: 50**

Order data

Order number	554063 50
GTIN	30048011603576
Item class	53M

Description

Version:

The Roloc™, Combidisc® CDR **quick-change system** with a plastic thread permits safe abrasive tool changing “with a single twist of the wrist” in a very short time.

Fleece disc **with aggressive Cubitron grit (CER)** in combination with wear-resistant fabric.

Application:

For efficient abrasion of small areas, even with changing contours. Reduced tool changing times save costs on multi-stage operations.

Allows **material removal** and **burr-free finishing** with only a single tool. High edge stability and long working life.

Note:

Roloc™ bristle discs can be found from No. 573510 onwards.

Technical description

Version	coarse super duty
Grit equivalent	50
Grit designation	extra coarse
Disc Ø	76.2 mm
Grinding media	Cubitron™ grinding grit

Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	Ø 76.2 mm
Manufacturer's designation	GB-DR
maximum speed	18000 min ⁻¹
Type of product	Non-woven abrasive

User data

	Suitability	V _c	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Stone	suitable only under restricted conditions		
Paint	suitable		
Uni	suitable		
wet maximum	suitable only under restricted conditions		
dry	suitable		

Accessories

Rubber backing pad shank Ø 6 mmmedium hard External Ø 75 mm	554093 75
Rubber backing pad with M14 mountinghard External Ø 75 mm	554094 75
Rubber backing pad shank Ø 6 mmsoft External Ø 75 mm	554091 75
Rubber backing pad shank Ø 6 mmmedium External Ø 75 mm	554092 75
Plastic backing pad shank Ø 6 mm External Ø 75 mm	554090 75
Rubber backing pad shank Ø 6 mmhard External Ø 75 mm	554089 75
Rubber backing pad with mounting M14hard External Ø 75 mm	554088 75