



Burr Tooth configuration STEEL – coarse, Carbide, Type: G0618



Order data

| | |
|--------------|---------------|
| Order number | 547100 G0618 |
| GTIN | 4007220936979 |
| Item class | 55F |

Description

Version:

The innovative tooth geometry permits **very high metal removal rates** combined with **smooth cutting and good guidance accuracy**. The optimised chip formation (no pointed chips) ensures good surface quality. Shank Ø 6 mm.

Application:

Optimised for **use on steel and steel castings**.

Shank Ø: 6 mm

Shape description: Pointed arch

Head Ø: 6 mm

Head length: 18 mm

Overall length: 55 mm

Shank Ø: 6 mm

Technical description

| | |
|---------------------------|--------------|
| Head Ø | 6 mm |
| Toothing grit designation | coarse |
| Shape description | Pointed arch |
| Tooth type abbreviation | STEEL |
| Shape | G0618 |
| Overall length | 55 mm |
| Shank Ø | 6 mm |
| Head length | 18 mm |

| | |
|-----------------|---------|
| Tool material | Carbide |
| Type of product | Burr |

User data

| | Suitability | V_c | ISO code |
|--------------------------------|--------------------|----------------------|-----------------|
| Steel < 900 N/mm ² | suitable | | |
| Steel < 1400 N/mm ² | suitable | | |
| Steel < 55 HRC | suitable | | |
| Steel < 60 HRC | suitable | | |
| Steel < 67 HRC | suitable | | |
| GG(G) | suitable | | |