

Flap wheel (A), 40 grit, Head Ø×head width: 60X50mm



Order data

Order number	554095 60X50		
GTIN	4045197525789		
Item class	52E		

Description

Version:

Flap strips bonded on to the shank of the tool.

Abrasive strips covered with regular Aluminium Oxide (A).

Application:

Primarily for finish grinding and polishing tasks on larger radii in tool and mould making, for vessel and machine fabrication. The abrasive strips adapt to the contours of the component.

Technical description

recommended speed	8000 min ⁻¹		
Grit	40		
Head width	50 mm		
maximum speed	8500 min ⁻¹		
Shank Ø	6 mm		
Head ∅	60 mm		



Grinding media	Aluminium Oxide grit (A)		
Grinding medium code	Α		
Product name attribute	40 grit		
Type of product	Flap wheel		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable only under restricted conditions		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable only under restricted conditions		
GG(G)	suitable only under restricted conditions		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
dry	suitable		