

### Flap wheel Fleece (A), coarse, Head Ø×head width: 80X50mm



### **Order data**

| Order number | 554950 80X50  |  |  |
|--------------|---------------|--|--|
| GTIN         | 4045197241207 |  |  |
| Item class   | 52E           |  |  |

### **Description**

#### **Version:**

Flap strips of fleece around the shank of the tool. Shank  $\emptyset$  6 mm.

Fleece impregnated with Aluminium Oxide (A). Creates a consistent matt finish.

#### **Application:**

For removal of dirt and oxide layers on metals as well as for matt finishing of Cr-Ni, other stainless steels, and also non-ferrous metals.

## **Technical description**

| maximum speed        | 7000 min <sup>-1</sup> |  |  |
|----------------------|------------------------|--|--|
| Head width           | 50 mm                  |  |  |
| recommended speed    | 4000 min <sup>-1</sup> |  |  |
| Shank Ø              | 6 mm                   |  |  |
| Head ∅               | 80 mm                  |  |  |
| Grinding medium code | A                      |  |  |
| Grit equivalent      | 100                    |  |  |
| Grit designation     | coarse                 |  |  |



| Product name attribute | coarse     |  |
|------------------------|------------|--|
| Type of product        | Flap wheel |  |

# **User data**

|                                | Suitability                               | $\mathbf{V}_{c}$ | ISO code |
|--------------------------------|---|------------------|----------|
| Alu Mg                         | suitable only under restricted conditions |                  |          |
| Steel < 900 N/mm <sup>2</sup>  | suitable                                  |                  |          |
| Steel < 1400 N/mm <sup>2</sup> | suitable                                  |                  |          |
| Steel < 55 HRC                 | suitable                                  |                  |          |
| Steel < 60 HRC                 | suitable only under restricted conditions |                  |          |
| Steel < 67 HRC                 | suitable only under restricted conditions |                  |          |
| INOX                           | suitable                                  |                  |          |
| Ti                             | suitable only under restricted conditions |                  |          |
| GG(G)                          | suitable                                  |                  |          |
| CuZn                           | suitable                                  |                  |          |
| Plastic, GRP                   | suitable                                  |                  |          |
| Wood                           | suitable                                  |                  |          |
| Paint                          | suitable only under restricted conditions |                  |          |
| dry                            | suitable                                  |                  |          |