

Coarse cleaning disc (SiC), Disc Ø: 115mm



Order data

Order number	566750 115		
GTIN	4045197566102		
Item class	52E		

Description

Version:

Cleaning discs with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad.

Very **coarse non-woven abrasive mesh structure**, will not clog even when used on soft thick coatings.

Hard and aggressive fleece body for **general-purpose use** on large areas.

Application:

For rust removal, paint removal, dressing weld seams and removing surface dirt.

With glass fibre backing pad for direct clamping on angle grinders.

Note:

For deburring wheels for double-ended bench grinding machines, see No. 556270 onwards.

Technical description

recommended speed	5000 - 7000 min ⁻¹	
Bore Ø	22.23 mm	
maximum speed	11000 min ⁻¹	
Disc Ø	115 mm	

Grinding medium code	SiC		
Degree of hardness	hard		
Grit designation	very coarse		
Iron, sulphur and chlorine constituents	< 0.1 %		
Shape description	flat		
maximum circumferential speed	60 m/s		
Type of product	Rough cleaning non- woven abrasive mesh		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable		
Plastic, GRP	suitable		
Wood	suitable		
Paint	suitable		
Uni	suitable		
wet maximum	suitable only under restricted conditions		
dry	suitable		

