Garant

Precision revolving lathe centre with extended point, very large \emptyset / Morse taper: 64/3



Order data

Order number	321360 64/3
GTIN	4045197880789
Item class	31Z

Description

Version:

- Tool fully hardened and ground.
- · Bearings designed to take high axial forces.
- · Maintenance-free greased for life.
- · Shaft seal prevents ingress of dirt and cooling fluids.

Description:

Lathe centres are mainly used on lathes to support long and slim workpieces, since with these workpieces there would otherwise be a risk of the workpiece bending or moving around as a result of the forces generated.

The lathe centre is secured with a Morse taper. The workpiece is clamped in the chuck and a counterbore is added using a centre drill. After re-clamping, the lathe centre is then inserted. **Application:**

· Combi tool for standard centring and machining pipes.

· Perfect all-purpose tip for general use on manual and CNC machines.

smallest Ø d: 16 mm reduced head length L₁: 78 mm Head length L: 100 mm maximum radial run-out: 0.005 mm maximum speed: 3800 min⁻¹ for workpiece weight: 330 kg

Technical description

maximum speed

3800 min⁻¹

maximum radial run-out	0.005 mm
for workpiece weight	330 kg
Head length L	100 mm
Taper angle a	60 °
reduced head length L ₁	78 mm
smallest Ø d	16 mm
Type of product	Centring drill