

**Linishing belt Cubitron™II 994F, 75×2000 mm, Grit: 36****Order data**

Order number	558445 36
GTIN	4046719801565
Item class	53S

Description**Version:**

Cubitron™ II linishing belt 994F with pure precision-shaped ceramic grit on extremely stable ZF polyester backing. High-performance linishing belt with high edge stability for **chamfering work and heavy-duty material removal** on **aluminium** (with abrasion grease No. 558190 ALU) and **steel**. Cool cutting thanks to grinding aids.

ZF polyester fabric (very robust) with high edge stability, no loss of profile. **Specially for linishing aluminium.**

Note:

Other grit sizes, qualities, and dimensions are available on request in line with the manufacturer's minimum order quantities. Unless specified otherwise on the order, belts will be supplied with standard joints. See No. 568526ff for spare linishing belts for burnishing machines.

Technical description

Grit	36
Series	Cubitron™II 994F
Grinding media	Ceramic grit

Grinding medium code	Ceramic
Iron, sulphur and chlorine constituents	< 0.1 %
Linishing belt width	75 mm
Linishing belt length	2000 mm
Product name attribute	75×2000 mm
Type of product	Linishing belt

User data

	Suitability	V _c	ISO code
Alu Mg	suitable	35-40 m/s	
Steel < 900 N/mm ²	suitable	32-38 m/s	P
Steel < 1400 N/mm ²	suitable	20-25 m/s	P
Steel < 55 HRC	suitable	32-38 m/s	H
Steel < 60 HRC	suitable	25-30 m/s	H
wet maximum	suitable only under restricted conditions		
dry	suitable		