



Torque screwdriver TorqueVario®, maximum torque: 700cNm



Order data

Order number	659930 700
GTIN	4010995264642
Item class	63K

Description

Version:

Numerical display of the torque value via scale in the window (40 – 50 individual values, depending on the torque range). Torque continuously adjustable using Torque-Setter (included). On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then immediately ready for use again. Accuracy class $\pm 6\%$.

Application:

For checking threaded fastenings to the specified torque, in combination with a Wiha Torque interchangeable bit No. 659932 – 659946.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Setting standard for size 60-700: No. 659931 size1 and for size 1400: No. 659931 size 2.

Technical description

Torque range	200 - 700 cNm
Torque range	2 - 7 Nm
maximum torque	800 cNm
Display	analogue
Torque measuring accuracy	$\pm 6\%$
Ø	41 mm

Trigger principle	mechanical short-travel release
Reversible reading	Nm
Measurement process	Torque
Setting the trigger value	with adjustment scale
Weight	320 g
Feedback	triggering
Adjustable trigger value	preset
Connection format	exchangeable blade
Standard	DIN EN ISO 6789
Overall length L	142 mm
Series	TorqueVario®
Calibration	O1
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Scale graduation, 1 graduation =	0.2 Nm
Manufacturer's designation	TorqueVario®-S
Torque fixed setting	no
Type of product	Torque screwdriver

Services

CalibrationTorque screwdriver maximum torque 0,04-20 N·m	020200 0,04-20
--	----------------

Accessories

Adjustment tool Torque Setter Type 1	659931 1
--------------------------------------	----------

