

# **GARANT Master Tap machine tap IC / Form B 6HX, AlTiX, M: M8**



### **Order data**

Order number	132723 M8
GTIN	4045197900319
Item class	111

### **Description**

#### **Version:**

**Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

#### With internal coolant feed.

Thread type: M

Tool material: HSS E PM Standard: DIN 371

Tolerance class: ISO 2X 6HX Thread pitch: 1.25 mm Overall length L: 90 mm Shank Ø D<sub>s</sub>: 8 mm

Shank square  $\square$ : 6.2 mm Tapping hole  $\varnothing$ : 6.8 mm

### **Technical description**

Shank square □	6.2 mm
Tapping hole Ø	6.8 mm
Thread pitch	1.25 mm
Shank Ø D <sub>s</sub>	8 mm
Tool material	HSS E PM
Number of clamping slots	3

Standard	DIN 371		
Tolerance class	ISO 2X 6HX		
Overall length L	90 mm		
Thread Ø	8 mm		
Number of cutting edges Z	3		
Thread depth	24 mm		
Thread type	M		
Thread size	M8		
Coating	AlTiX		
Flank angle	60 °		
Thread standard	DIN 13		
Taper lead form	В		
Shank	Plain shank with h9		
Through-coolant	yes		
Application for type of drilling	up to 3×D for through holes		
Cutting direction	right-hand		
Type of threading tool	Machine tap for dynamic machining		
Colour ring	green		
Series	Master Tap		
Type of product	Тар		

## **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Alu plastics	suitable	30 m/min	N
Aluminium (short chipping)	suitable	35 m/min	N
Alu > 10% Si	suitable	20 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	30 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	30 m/min	Р

Steel < 900 N/mm <sup>2</sup>	suitable	25 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	12 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	8 m/min	Р
INOX < 900 N/mm <sup>2</sup>	suitable	10 m/min	М
INOX > 900 N/mm <sup>2</sup>	suitable	8 m/min	М
GG(G)	suitable	20 m/min	K
CuZn	suitable	20 m/min	N
Uni	suitable		
Oil	suitable		
wet maximum	suitable		