

GARANT Master Tap machine tap HSS-E-PM, AITIX, G: G3/8



Order data

Order number	133330 G3/8
GTIN	4045197901163
Item class	111

Description

Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Tool material: HSS E PM Threads per inch: 19 Thread Ø: 16.66 mm Overall length L: 100 mm Shank Ø D₅: 12 mm Shank square □: 9 mm Tapping hole Ø: 15.25 mm

Technical description

Thread pitch	1.337 mm
Thread depth	49.98 mm
Tapping hole Ø	15.25 mm
Number of cutting edges Z	2
Shank Ø D _s	12 mm

Number of clamping slots	2	
Threads per inch	19	
Shank square □	9 mm	
Thread Ø	16.66 mm	
Tool material	HSS E PM	
Overall length L	100 mm	
Thread size	G3/8	
Series	Master Tap	
Coating	AlTiX	
Thread type	G	
Flank angle	55 °	
Standard	DIN 5156	
Taper lead form	В	
Shank	Plain shank with h9	
Through-coolant	no	
Application for type of drilling	up to 3×D for through holes	
Cutting direction	right-hand	
Type of threading tool	Machine tap for dynamic machining	
Colour ring	green	
Type of product	Тар	

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu plastics	suitable	30 m/min	N
Aluminium (short chipping)	suitable	35 m/min	N
Alu > 10% Si	suitable	20 m/min	N
Steel < 500 N/mm ²	suitable	30 m/min	Р
Steel < 750 N/mm ²	suitable	30 m/min	Р

Steel < 900 N/mm ²	suitable	25 m/min	Р
Steel < 1100 N/mm ²	suitable	12 m/min	Р
Steel < 1400 N/mm ²	suitable	8 m/min	Р
INOX < 900 N/mm ²	suitable	10 m/min	М
INOX > 900 N/mm ²	suitable	8 m/min	М
GG(G)	suitable	20 m/min	K
CuZn	suitable	20 m/min	N
Uni	suitable		
Oil	suitable		
wet maximum	suitable		