

Garant
Solid carbide mini milling cutter, AlCrN, Ø e8 DC: 0,8mm

Order data

Order number	GG1264 0,8
GTIN	4045197906847
Item class	GGN

Description
Version:

Shank similar to **DIN 6535 HB**. Improved coating for general-purpose applications in steel and cast iron.

Same as No. 202264.

Technical description

Cutting edge Ø D _c	0.8 mm
Flute length L _c	2 mm
Shank form	HA
Shank	DIN 6535 HA to h6
Overall length L	38 mm
No. of teeth Z	3
Shank Ø D _s	3 mm
Feed f _z for side milling in steel < 750 N/mm ²	0.003 mm
Helix angle	45 degrees
Feed f _z for slot milling in steel < 750 N/mm ²	0.003 mm

Direction of infeed	horizontal, oblique and vertical
Tolerance nominal \varnothing	e8
Contents	5
Coating	AlCrN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
Aluminium (short chipping)	suitable	280 m/min	N
Alu > 10% Si	suitable	200 m/min	N
Steel < 500 N/mm ²	suitable	120 m/min	P
Steel < 750 N/mm ²	suitable	110 m/min	P
Steel < 900 N/mm ²	suitable	100 m/min	P
Steel < 1100 N/mm ²	suitable	70 m/min	P
Steel < 1400 N/mm ²	suitable	60 m/min	P
INOX < 900 N/mm ²	suitable	70 m/min	M
INOX > 900 N/mm ²	suitable	50 m/min	M
GG(G)	suitable	90 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		
dry	suitable only under restricted conditions		

Air

suitable

Accessories

Solid carbide mini milling cutter Ø e8 DC 0,8 mm

202264 0,8