

Torque wrench with dial gauge display, maximum torque: 2100N·m

Order data

Order number	655500 2100
GTIN	2050001017031
Item class	66F

Description

Version:

One-armed; slim design with easily readable dial gauge. Body entirely of steel, chrome-plated with fixed square drive for plug-in heads.

Units of measure: Nm.

Function:

Actual torque can be read on the gauge whilst working; the final value is held by the memory pointer to be read later.

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Cutting dataa:

Legend for drawing and formula:

- I_1 = Lever length without plug-in head
- I_2 = Adjusted reference dimension on the torque wrench
- I_3 = Lever length including factory calibration reference dimension
- I_4 = Reference dimension of the plug-in head
- L = Total length of the tool
- $T_1 =$ Torque to be set

 T_2 = Specified torque

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Technical description

Weight

12000 g

maximum torque	2100 Nm
Display	analogue
Square drive	1 in
Torque measuring accuracy	±3 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	20 Nm
Torque range	200 - 2100 Nm
Setting the trigger value	Memory pointer
Lever length including factory calibration reference dimension $[I_3]$	2000 mm
Standard	DIN EN ISO 6789
Overall length L	2140 mm
Reversible reading	Nm
Feedback	displaying
Measurement process	Torque
Connection format	Push-through square drive (ratchet)
Adjustable trigger value	non-adjustable
Calibration	03
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	visual
Measurement technology	mechanical
Deflection function	no
Slipper function	no
Quick release/ quick-change function	no
Memory pointer	yes
Type of product	Torque Wrench