

Torque wrench with reversible ratchet, maximum torque: 2000N·m



Order data

Order number	656500 2000
GTIN	4000896177776
Item class	630

Description

Version:

Handy and very compact single-arm torque wrench, adjustable by scale and self-triggering. Extremely high repeat accuracy, since high quality materials are used throughout. Wearing parts, such as compression springs, are specially pre-treated and sorted. Reversible ratchet for left-hand and right-hand tightening.

With built-in reversible ratchet – for left and right hand tightening.

Units of measure: Nm **3-piece** with release tool in nylon carrying bag.

Function:

The wrench triggers giving a "signal" (clearly audible acoustic tone and noticeable vibration) and afterwards is immediately ready for use again.

Application:

For medium to larger batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

Of the displayed value only for right-hand tightening: $\pm 4 \%$.

Cutting dataa:

Legend for drawing and formula:

 I_1 = Lever length without plug-in head

 I_2 = Adjusted reference dimension on the torque wrench

 I_3 = Lever length including factory calibration reference dimension

 I_4 = Reference dimension of the plug-in head

L = Total length of the tool

 T_1 = Torque to be set



T_2 = Specified torque

Note:

Calibration is only possible for right-hand tightening.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Technical description

Weight	18000 g
maximum torque	2000 Nm
Display	analogue
Square drive	1 in
Torque measuring accuracy	±4 %
Direction of tightening	For right and left-hand tightening
Scale graduation, 1 graduation =	6 Nm
Torque range	800 - 2000 Nm
Measurement process	Torque
Overall length L	3033 mm
Standard	DIN EN ISO 6789
Setting the trigger value	with adjustment scale
Feedback	triggering
Connection format	Push-through square drive (ratchet)
Trigger principle	mechanical short-travel release
Adjustable trigger value	adjustable
Lever length including factory calibration reference dimension [I ₃]	2926 mm
Reversible reading	Nm
Calibration	01
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk



Measurement technology	mechanical
Type of product	Torque Wrench
Services	
CalibrationTorque wrench maximum torque 2000 N·m	020010 2000