Your Torque Partner

Torque wrench with setting scale, maximum torque: 2100N·m



Order data

Order number	657235 2100
GTIN	4571141276457
Item class	66F

Description

Version:

Torque wrench, adjustable using micrometer scale, with protection against accidental changes to the setting. With reversible ratchet head and square drive for sockets.

Units of measure: Nm. With knurled metal handle.

Function:

On reaching the set torque value the wrench triggers giving a "signal" (acoustic and perceptible) and is then immediately ready for use again.

Application:

For medium and large batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Cutting dataa:

Legend for drawing and formula:

- I_1 = Lever length without plug-in head
- I_2 = Adjusted reference dimension on the torque wrench
- I_3 = Lever length including factory calibration reference dimension
- I_4 = Reference dimension of the plug-in head
- L = Total length of the tool
- $T_1 =$ Torque to be set
- $T_2 =$ Specified torque

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789. Use only sockets with lock hole.

Technical description

maximum torque

2100 Nm

Square drive	1 in
Weight	17000 g
Display	analogue
Torque measuring accuracy	±3 %
Direction of tightening	Right-hand tightening
Scale graduation, 1 graduation =	10 Nm
Torque range	500 - 2100 Nm
Setting the trigger value	with adjustment scale
Connection format	Push-through square drive (ratchet)
Overall length L	1899 mm
Measurement process	Torque
Trigger principle	mechanical short-travel release
Reversible reading	Nm
Standard	DIN EN ISO 6789
Feedback	triggering
Lever length including factory calibration reference dimension [I ₃]	1750 mm
Adjustable trigger value	adjustable
Calibration	01
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque Wrench