

Deflecting torque wrench with scale, maximum torque: 5N·m



Order data

Order number	657735 5
GTIN	4045197684806
Item class	61E

Description

Version:

One-armed torque wrench, adjustable by a scale, self-triggering. **The trigger mechanism makes unintentional overtightening extremely unlikely. Anti-clockwise tightening** by reversing the plug-in head.

Units of measure: Nm

Function:

On reaching the preset torque value the wrench triggers a clearly detectable deflection and is then immediately ready for use again. The long-travel indication gives the user an unmistakable signal that the set torque has been reached.

Application:

For controlled tightening of screws to a pre-set torque during batch productions.

Standard:

Geprüft nach DIN EN ISO 6789.

Accuracy:

±6 % of the set value.

Note

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789. Suitable spare jaws No. 657582 - 657950.

Technical description

Display	analogue
maximum torque	5 Nm
Weight	290 g
Socket for plug-in head	9×12 mm

Torque measuring accuracy	±6 %
Direction of tightening	For right and left-hand tightening
Exchangeable tool	Plug-in head
Scale graduation, 1 graduation =	0.025 Nm
Torque range	1 - 5 Nm
Adjusted reference dimension on the torque wrench $[I_2]$	18.3 mm
Adjustable trigger value	adjustable
Measurement process	Torque
Standard	DIN EN ISO 6789
Reversible reading	Nm
Lever length without plug-in head [I ₁]	191.5 mm
Setting the trigger value	with adjustment scale
Overall length L	222 mm
Connection format	for plug-in heads (rectangular socket)
Lever length including factory calibration reference dimension [I ₃]	191.3 mm
Trigger principle	mechanical long-travel release
Feedback	triggering
Calibration	01
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	optisk
Release signalling	haptisk
Deflection function	yes
Type of product	Torque Wrench
Comicos	

Services

DAkkS calibrationTorque wrench maximum torque 1000 N·m

020020 1000

CalibrationTorque wrench maximum torque 400 N·m	020010 400
Accessories	
Plug-in ratchet Type-Square drive 1-1/2 in	657630 1-1/2
Plug-in ratchet Type-Square drive 1-1/4 in	657630 1-1/4
Plug-in ratchet reversible Type-Square drive 1-3/8 in	657582 1-3/8
Plug-in ratchet reversible Type-Square drive 1-1/4 in	657582 1-1/4
Plug-in ratchet Type-Square drive 1-3/8 in	657630 1-3/8
Plug-in ratchet reversible Type-Square drive 1-1/2 in	657582 1-1/2