

Torque screwdriver with scale, maximum torque: 600cNm



Order data

Order number	659945 600
GTIN	4045197514028
Item class	62E

Description

Version:

Practical handle for transmission of the required torques without problems. Easy to read micrometer scale, protected against dirt. Lock at the end of the handle against inadvertent adjustment. Interchangeable blade to take 1/4 inch bits included.

Function:

On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use.

Application:

For controlled tightening of screws to a pre-set torque.

Standard:

Geprüft nach DIN EN ISO 6789.

Note

All Wiha interchangeable blades (No. 659940 – 659946) can also be used in the Holex torque screwdriver No. 659945.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Technical description

Display	analogue
Scale graduation, 1 graduation =	20 cNm
maximum torque	600 cNm
Torque measuring accuracy	±6 %
Bit socket	D 6,3

Trigger principle	mechanical slip clutch
Connection format	Bit holder 1/4 inch
Setting the trigger value	with adjustment scale
Weight	300 g
Reversible reading	cNm
Reversible reading	Nm
Measurement process	Torque
Standard	DIN EN ISO 6789
Feedback	triggering
Overall length L	153 mm
Calibration	01
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	acoustic
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

CalibrationTorque screwdriver maximum torque 0,04-20 N·m

020200 0,04-20

Accessories

Interchangeable blade 1/4 inch	659947
Torque interchangeable bladefor Phillips Cross-head size 0	659940 0

Torque interchangeable bladePozidriv Cross-head size 0	659941 0
Torque interchangeable bladePozidriv Cross-head size 1	659941 1
Torque interchangeable bladefor Phillips Cross-head size 1	659940 1