

KANON
Torque screwdriver with scale, maximum torque: 30cNm

Order data

Order number	659949 30
GTIN	4580125347717
Item class	66F

Description
Version:

Setting using a micrometer scale. Profiled light alloy handle.

Function:

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3

Torque measuring accuracy: $\pm 6\%$

Overall length L: 107 mm

Torque range: 2 - 30 cNm

Torque range: 0.02 - 0.3 N·m

Scale graduation, 1 graduation =: 0.2 cNm

Ø: 16 mm

Technical description

maximum torque	30 cNm
Ø	16 mm

Scale graduation, 1 graduation =	0.2 cNm
Display	analogue
Torque measuring accuracy	±6 %
Bit socket	F 6.3
Torque range	2 - 30 cNm
Torque range	0.02 - 0.3 N·m
Overall length L	107 mm
Setting the trigger value	with adjustment scale
Trigger principle	mechanical short-travel release
Standard	DIN EN ISO 6789
Measurement process	Torque
Weight	60 g
Reversible reading	cNm
Adjustable trigger value	adjustable
Connection format	Bit holder 1/4 inch
Feedback	triggering
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

Labellinglaser-etched Type	018940
CalibrationTorque wrench both ends maximum torque 400/2 N·m	020030 400/2

