

**Garant**
**Solid carbide milling cutter, AlCrN, Ø e8 DC: 8,5 mm**

**Order data**

Order number	202268 8,5
GTIN	4045197930781
Item class	11X

**Description**
**Version:**

Dimensions similar to **DIN 6527**.

Improved coating for general-purpose applications in steel and cast iron.

**Note:**
**Successor product to No. 202080.**

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length  $L_c$ : 19 mm

Overhang length  $L_1$  incl. recess: 32 mm

Recess Ø  $D_1$ : 8.3 mm

Overall length L: 72 mm

Shank Ø  $D_s$ : 10 mm

**Technical description**

Corner chamfer width at 45°	0.1 mm
Flute length $L_c$	19 mm
Feed $f_z$ for side milling in steel < 750 N/mm <sup>2</sup>	0.08 mm
Overall length L	72 mm
Overhang length $L_1$ incl. recess	32 mm

Helix angle	30 degrees
No. of teeth Z	3
Shank	DIN 6535 HB to h6
Cutting edge $\varnothing D_c$	8.5 mm
Recess $\varnothing D_1$	8.3 mm
Shank $\varnothing D_s$	10 mm
Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.05 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal $\varnothing$	e8
Corner chamfer angle	45 degrees
Coating	AlCrN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Cutting width $a_e$ for milling operation	0.3×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	without
Type of product	End mill