


## Garant

### GARANT Master Steel solid carbide finishing cutter HPC, TiAlN, Ø f8 DC: 6mm



## Order data

Order number	204015 6
GTIN	4045197951892
Item class	11X

## Description

### Version:

For **finishing operations**.

Special geometry for optimum chip evacuation.

Unequal spacing gives high **intrinsic stability and smooth cutting action**.

For **profile milling as a finishing operation**.

Suitable for machining titanium and titanium alloys.

### Note:

Can be reground from  $\varnothing D_c = 6 \text{ mm}$ .

$a_{e \max} = 0.1 \times D$

## Technical description

Cutting edge $\varnothing D_c$	6 mm
Balance quality with shank	G 2.5 with HA
Direction of infeed	horizontal
Helix angle	45 degrees
No. of teeth Z	7
Flute length $L_c$	18 mm
Tolerance nominal $\varnothing$	f8
Shank	DIN 6535 HA to h6
Shank $\varnothing D_s$	6 mm
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.035 mm

Overall length L	62 mm
Corner chamfer angle	90 degrees
Series	Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	$0.1 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End / face mill

## User data

	Suitability	$V_c$	ISO code
Steel < 500 N/mm <sup>2</sup>	suitable	360 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	340 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	300 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	290 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	200 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable	130 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	120 m/min	M
Ti > 850 N/mm <sup>2</sup>	suitable only under restricted conditions	100 m/min	S
GG(G)	suitable	300 m/min	K
wet maximum	suitable only under restricted conditions		
wet minimum	suitable only under restricted conditions		

dry	suitable only under restricted conditions
<del>Air</del> <b>Services</b>	<del>suitable</del>
Shank grinding Type HB	129100 HB