

Garant

GARANT Master TM plain shank thread mill with countersink 2×D, TiAlN, MF: 14X1,5



Order data

Order number	139682 14X1,5
GTIN	4045197957979
Item class	11D

Description

Version:

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve very **smooth running** and **long tool life**.

Newly developed universal geometry and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing.**
- **Increased number of cutting edges.**
- **New coating for optimum wear resistance.**
- **Corrected thread profile for avoidance of profile distortions.**

Advantage:

Incorporating a countersink profile for a 90° countersink and thread milling in a single operation.

Note:

HB and HE shanks are available at the same price as HA.

Order **HB** shank: with **No. 139682 + 129100 HB**

Order **HE** shank: with **No. 139682 + 129100 HE**

Through-coolant: yes

No. of teeth Z: 6

Thread pitch: 1.5 mm

Nominal $\varnothing D_c$: 12 mm

Flute length L_c : 29.25 mm

Shank length L_s : 48 mm

Overall length L: 106 mm

Shank $\varnothing D_s$: 16 mm

Technical description

Overall length L	106 mm
Shank $\varnothing D_s$	16 mm
Feed f_z in steel < 750 N/mm ²	0.1 mm
Through-coolant	yes
Thread pitch	1.5 mm
No. of teeth Z	6
Thread depth	28 mm
Shank length L_s	48 mm
Number of clamping slots	6
Thread size	M14×1.5
Nominal $\varnothing D_c$	12 mm
Flute length L_c	29.25 mm
Programming value for countersink L_1	30.5 mm
Neck $\varnothing D_1$	14.5 mm
Coating	TiAlN
Thread type	MF
Thread type	MF-LH
Flank angle	60 °
Tool material	Solid carbide
Thread standard	DIN 13
Shank	DIN 6535 HA to h6
Application for type of drilling	up to 2×D for blind holes
Application for type of drilling	up to 2×D for through holes
Spacing of the cutters	unequal spacing
Countersink angle	90 °
Colour ring	green
Internal/external application	Internal
Series	Master TM
Type of product	thread milling cutter

User data

	Suitability	V _c	ISO code
Alu plastics	suitable	220 m/min	N
Aluminium (short chipping)	suitable	220 m/min	N
Alu > 10% Si	suitable	180 m/min	N
Steel < 500 N/mm ²	suitable	140 m/min	P
Steel < 750 N/mm ²	suitable	130 m/min	P
Steel < 900 N/mm ²	suitable	120 m/min	P
Steel < 1100 N/mm ²	suitable	90 m/min	P
Steel < 1400 N/mm ²	suitable	80 m/min	P
Steel < 50 HRC	suitable only under restricted conditions	45 m/min	H
TOOLOX 33	suitable	85 m/min	H
TOOLOX 44	suitable	50 m/min	H
INOX < 900 N/mm ²	suitable	82 m/min	M
INOX > 900 N/mm ²	suitable	75 m/min	M
Ti > 850 N/mm ²	suitable	50 m/min	S
GG(G)	suitable	120 m/min	K
CuZn	suitable	200 m/min	N
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		
Air	suitable		

Services

Shank grinding Type HE	129100 HE
Shank grinding Type HB	129100 HB

