

Rough grinding disc "2 in 1", Disc Øxdisc width: 115X6mm



Order data

Order number	GG5050 115X6
GTIN	4045197191700
Item class	GGN

Description

Version:

Open homogeneous structure; low odour grinding; glass fibre reinforcing fabric for maximum work safety; cool grinding; bore \varnothing 22.23 mm. The iron, sulphur and chlorine content are less than 0.1 %, making them suitable for working stainless steels (INOX). For use on electric and pneumatic angle grinders.

- Grit, bonding, abrasive additives as well as reinforcement of the rough grinding discs are optimised for maximum metal removal rate and working life in their respective applications.
- · Shapes: Rough grinding discs, depressed centres (shapes 27, 28, 29)
- · Grinding angle 20° to 30°
- Application: On electric and pneumatic angle grinders with maximum 80 m/s circumferential speed for grinding welds, surfaces, and edges.

Rough grinding disc for **steel and stainless steel** with **long working life** and high metal removal rate.

Specification:

A30Q-BF (same as 560500) for steel and stainless steel with long working life and high metal removal rate.

Note:



Only sold in bulk pack quantities, not supplied individually. Ordering information: 1 set = 1 bulk pack.

Technical description

Bore Ø	22.23 mm	
Disc thickness	6 mm	
maximum speed	13300 min ⁻¹	
Disc Ø	115 mm	
Contents	40	
Grinding medium code	Α	
Specification	A30Q-BF	
Iron, sulphur and chlorine constituents	< 0.1 %	
recommended approach angle	20-30 degrees	
optimised for material	INOX	
optimised for material	Steel	
maximum circumferential speed	80 m/s	
Type of product	Rough grinding disc	

User data

	Suitability	V _c	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable only under restricted conditions		
INOX	suitable only under restricted conditions		

Ti	suitable only under restricted conditions	
GG(G)	suitable only under restricted conditions	
CuZn	suitable only under restricted conditions	
Plastic, GRP	suitable only under restricted conditions	
dry	suitable	

Accessories

Rough grinding disc"2 in 1" Disc Ø×disc width 115X6 mm

560500 115X6