

# **TMSERROR, Fleece structure: 280**



## **Order data**

| Order number | GG5115 280    |
|--------------|---------------|
| GTIN         | 4045197575043 |
| Item class   | GGN           |

### **Description**

#### **Version:**

**Synthetic nylon fleece impregnated with abrasive grit** in synthetic resin bonding. Contains no materials that could cause corrosion, for wet and dry use (same as 556015; 556110; 556115).

similar to 556115.

#### **Advantage:**

- · Adapts to the component shape.
- The open structure prevents clogging and reduces heat development.
- · Even and reproducible finish.
- · Can be used wet or dry.
- · Contains no materials that could cause corrosion.

#### **Application:**

Can be used by hand, on hand block No. 556020 or on an orbital sander. **Medium / medium fine:** Can be used universally for removing rust film, light soiling, discolouration; for rubbing down ground or brushed surfaces, or for degreasing and cleaning prior to painting.

#### **Content:**

4 rollers / bulk pack.

Note:



Only sold in bulk pack quantities, not supplied individually. Ordering information: 1 set = 1 bulk pack.

# **Technical description**

| Grit designation                        | medium fine             |  |
|---|-------------------------|--|
| Grit equivalent                         | 280 - 360               |  |
| Colour                                  | red                     |  |
| Version                                 | A Very Fine             |  |
| Fleece structure                        | 280                     |  |
| Contents                                | 4                       |  |
| Iron, sulphur and chlorine constituents | < 0.1 %                 |  |
| Roller width                            | 115 mm                  |  |
| Roll length                             | 10 m                    |  |
| Product name attribute                  | 115 mm × 10 m           |  |
| Type of product                         | Roll of abrasive fleece |  |

# **User data**

|                                | Suitability | $\mathbf{V}_{c}$ | ISO code |
|--------------------------------|-------------|------------------|----------|
| Alu Mg                         | suitable    |                  |          |
| Steel < 900 N/mm <sup>2</sup>  | suitable    |                  |          |
| Steel < 1400 N/mm <sup>2</sup> | suitable    |                  |          |
| Steel < 55 HRC                 | suitable    |                  |          |
| Steel < 60 HRC                 | suitable    |                  |          |
| Steel < 67 HRC                 | suitable    |                  |          |
| INOX                           | suitable    |                  |          |
| Ti                             | suitable    |                  |          |
| GG(G)                          | suitable    |                  |          |
| CuZn                           | suitable    |                  |          |
| Plastic, GRP                   | suitable    |                  |          |

| Wood        | suitable                                  |  |
|-------------|---|--|
| Stone       | suitable only under restricted conditions |  |
| Paint       | suitable                                  |  |
| Uni         | suitable                                  |  |
| wet maximum | suitable only under restricted conditions |  |
| dry         | suitable                                  |  |

# Accessories

Roll of abrasive fleece Fleece structure 280

556115 280