Wide-span basic rack, Depth 500 mm, Height / Shelf width: 2500/2250mm



Order data

Order number	990710 2500/2250
GTIN	4004514215079
Item class	96P

Description

Version:

Galvanised T-profile frames. With MULTI^{plus} 250 galvanised sheet metal storage shelves. Storage shelf levels adjustable at 25 mm intervals. Simple plug-in cross pieces ensure quick assembly. Maximum **load per shelf:** 400 kg. **Load per bay:** for height 2000 mm 1200 kg, for 2500 mm 1600 kg, for 3000 mm 2000 kg.

Description:

Assembled size:

Basic rack: Nominal length + 60 mm

Add-on rack: Nominal length + 6 mm

Overall depth of the rack: Nominal depth + 36 mm

Height of the cross beams: 65 mm

Application:

Storage of awkward and bulky goods. Access from both sides allows for short picking distances. **Note:**

The storage shelves are inserted in segments to suit the compartment width. Segments:
750 mm and 1000 mm.

- · Floor and wall fastenings are not included. Suitable floor anchoring No. 990854.
- Wide-span racking WS 2000 is compatible with storage shelf racking No. 990500 990554, to which other dimensions and components also relate. We will be happy to quote you further options. If you are interested, please contact us.

- The free unsupported length (K) must not be more than 600 mm. The permissible bay load must be reduced by the amount of this shelf.
- Supplied for self-assembly, saving freight costs. Delivered unassembled.

Technical description

Number of storage levels4Storage shelf depth500 mmHeight2500 mmRack installationBasic rackMaterial of storage levelGalvanised sheet metalAssembled size basic rack width2310 mmWidth2310 mmShelf width2250 mmDepth537 mmRack depth500 mmRack width2250 mmRack height500 mmShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf hickness40 mmCross beam height55 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialPlug-in rackingMaterialDevice with key	Customer assembly	yes
Height2500 mmRack installationBasic rackMaterial of storage levelGalvanised sheet metalAssembled size basic rack width2310 mmWidth2310 mmShelf width2250 mmDepth537 mmRack depth500 mmRack width2250 mmRack height500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf thickness400 mmCross beam height25 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Number of storage levels	4
Rack installationBasic rackMaterial of storage levelGalvanised sheet metalAssembled size basic rack width2310 mmWidth2310 mmShelf width2250 mmDepth537 mmRack depth500 mmRack width2250 mmRack height500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf thickness400 kgShelf thickness400 kgType of installation25 mmType of installationPlug-in rackingMaterial91 capacityMaterial91 capacityShelf load capacity65 mmShelf thickness91 capacityShelf thickness<	Storage shelf depth	500 mm
Material of storage levelGalvanised sheet metalAssembled size basic rack width2310 mmWidth2310 mmWidth2310 mmShelf width2250 mmDepth537 mmRack depth500 mmRack width2250 nmRack width2250 nmRack height200 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness40 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Height	2500 mm
Assembled size basic rack width2310 mmWidth2310 mmWidth2310 mmShelf width2250 mmDepth537 mmRack depth500 mmRack width2250 mmRack width2250 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 kgCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack installation	Basic rack
Width2310 mmShelf width2250 mmDepth537 mmRack depth500 mmRack width2250 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 kgCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Material of storage level	Galvanised sheet metal
Shelf width2250 mmDepth537 mmRack depth500 mmRack width2250 mmRack height2250 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Assembled size basic rack width	2310 mm
Depth537 mmRack depth500 mmRack width2250 mmRack height2250 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Width	2310 mm
Rack depth500 mmRack width2250 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 kgShelf thickness400 kgCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Shelf width	2250 mm
Rack width2250 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Depth	537 mm
Rack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack depth	500 mm
Shelf load capacity400 kgmaximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness400 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack width	2250 mm
maximum bay load1600 kgShelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness40 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack height	2500 mm
Shelf load capacity / maximum distributed shelf load (on metal)400 kgShelf thickness40 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Shelf load capacity	400 kg
metal)400 kgShelf thickness40 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	maximum bay load	1600 kg
Cross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised		400 kg
Height adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Shelf thickness	40 mm
Type of installationPlug-in rackingMaterialgalvanised	Cross beam height	65 mm
Material galvanised	Height adjustment interval	25 mm
	Type of installation	Plug-in racking
	Material	galvanised
Product name attribute Depth 500 mm	Product name attribute	Depth 500 mm
Type of product Wide-span racking	Type of product	Wide-span racking

Accessories

Sheet metal storage shelf galvanised Depth 500 mm	990800 500
Clamping base	990852