## Wide-span add-on rack, Depth 400 mm, Height / Shelf width: 2500/2500mm



## Order data

Order number	990745 2500/2500
GTIN	4004514201249
Item class	96P

### Description

#### Version:

Galvanised T-profile frames. With 19 mm chipboard shelves. Storage shelf levels adjustable at 25 mm intervals. Simple plug-in cross pieces ensure quick assembly. Maximum **load per shelf:** 400 kg. **Load per bay:** for height 2000 mm 1200 kg, for 2500 mm 1600 kg, for 3000 mm 2000 kg. **Description:** 

#### **Assembled size:**

**basic rack:** Nominal length + 60 mm

**Extension rack:** Nominal length + 6 mm

Overall depth of the rack: Nominal depth + 37 mm

Height of the cross beams: 65 mm

Note:

- The storage shelves are inserted in segments to suit the compartment width. Segments: 750 mm and 1000 mm.
- · Floor and wall fastenings are not included. Suitable floor anchoring No. 990854.
- Wide-span racking WS 2000 is compatible with storage shelf racking No. 990500 990554, to which other dimensions and components also relate. We will be happy to quote you further options. If you are interested, please contact us.
- The free unsupported length (K) must not be more than 600 mm. The permissible bay load must be reduced by the amount of this shelf.
- · Supplied for self-assembly, saving freight costs. Delivered unassembled.

# **Technical description**

Height2500 mmCustomer assemblyyesRack installationExtension rackNumber of storage levels4Material of storage levelChipboard shelfAssembled size add-on rack width2506 mmShelf width2500 mmStorage shelf depth400 mmDepth437 mmRack depth400 mmRack height2500 mmShelf vidth2500 mmInsert thickness1600 kgVorkbench/desk load capacity - maximum distributed load (on wood)1600 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingProduct name attributeDepth 400 mm	Width	2506 mm
Rack installationExtension rackNumber of storage levels4Material of storage levelChipboard shelfAssembled size add-on rack width2506 mmShelf width2500 mmStorage shelf depth400 mmDepth437 mmRack depth400 mmRack width2500 mmStorage shelf depth400 mmDepth400 mmRack depth400 mmRack depth400 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Height	2500 mm
Number of storage levels4Material of storage levelChipboard shelfAssembled size add-on rack width2506 mmShelf width2500 mmStorage shelf depth400 mmDepth437 mmRack depth2500 mmRack depth2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgVorkbench/desk load capacity - maximum distributed load (on wood)19 mmInsert thickness19 mmCross beam height25 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Customer assembly	yes
Material of storage levelChipboard shelfAssembled size add-on rack width2506 mmShelf width2500 mmStorage shelf depth400 mmDepth4337 mmRack depth400 mmRack width2500 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgInsert thickness19 mmCross beam height25 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack installation	Extension rack
Assembled size add-on rack width2506 mmShelf width2500 mmStorage shelf depth400 mmDepth437 mmRack depth400 mmRack width2500 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgVorkbench/desk load capacity - maximum distributed load (on wood)19 mmInsert thickness19 mmCross beam height25 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Number of storage levels	4
Shelf width2500 mmStorage shelf depth400 mmDepth437 mmRack depth400 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgVorkbench/desk load capacity - maximum distributed load (on wood)19 mmInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Material of storage level	Chipboard shelf
Storage shelf depth400 mmDepth437 mmRack depth400 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgVorkbench/desk load capacity - maximum distributed load (on wood)19 mmInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Assembled size add-on rack width	2506 mm
Depth437 mmRack depth400 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Shelf width	2500 mm
Rack depth400 mmRack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Storage shelf depth	400 mm
Rack width2500 mmRack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Depth	437 mm
Rack height2500 mmShelf load capacity400 kgmaximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack depth	400 mm
Shelf load capacity400 kgmaximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack width	2500 mm
maximum bay load1600 kgWorkbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Rack height	2500 mm
Workbench/desk load capacity - maximum distributed load (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Shelf load capacity	400 kg
Ioad (on wood)400 kgInsert thickness19 mmCross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	maximum bay load	1600 kg
Cross beam height65 mmHeight adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised		400 kg
Height adjustment interval25 mmType of installationPlug-in rackingMaterialgalvanised	Insert thickness	19 mm
Type of installationPlug-in rackingMaterialgalvanised	Cross beam height	65 mm
Material galvanised	Height adjustment interval	25 mm
<b>J</b>	Type of installation	Plug-in racking
Product name attribute Depth 400 mm	Material	galvanised
	Product name attribute	Depth 400 mm
Type of product Wide-span racking	Type of product	Wide-span racking

## Accessories

Chipboard shelf storage level Depth 400 mm

990825 400