

# GARANT Master Titan solid carbide finishing cutter HPC, uncoated, $\varnothing$ e8 DC: 6mm



#### **Order data**

Order number	2036346
GTIN	4045197991560
Item class	11Z

### **Description**

#### **Version:**

For finishing operations.

Special geometry for optimum chip evacuation.

Unequal spacing gives high intrinsic stability and smooth cutting action.

For profile milling as a finishing operation in titanium and titanium alloys.

#### **Advantage:**

Suitable for medical technology and approved for foodstuffs.

# **Technical description**

Flute length L <sub>c</sub>	24 mm	
No. of teeth Z	7	
Overall length L	66 mm	
Shank	DIN 6535 HA to h6	
Tolerance nominal Ø	e8	
Helix angle	40 degrees	
Cutting edge Ø D <sub>c</sub>	6 mm	
Feed $f_z$ for side milling in titanium > 850 N/mm <sup>2</sup>	0.024 mm	
Direction of infeed	horizontal	
Shank Ø D <sub>s</sub>	6 mm	
orner rounding r <sub>v</sub> 0.05 mm		

Series	Master Titan	
Coating	uncoated	
Tool material	Solid carbide	
Standard	Manufacturer's standard	
Туре	N	
Helix angle characteristic	unequal spacing	
utting width $a_e$ for milling operation 0.05×D for side mill		
Through-coolant	no	
Machining strategy	HPC	
Colour ring	pink	
Type of product	End / face mill	

# **User data**

	Suitability	<b>V</b> <sub>c</sub>	ISO code
Alu plastics	suitable only under restricted conditions	130 m/min	N
Aluminium (short chipping)	suitable only under restricted conditions	100 m/min	N
Alu > 10% Si	suitable only under restricted conditions	85 m/min	N
Ti > 850 N/mm <sup>2</sup>	suitable	60 m/min	S
wet maximum	suitable		

# **Services**

Shank grinding Type HB	129100 HB
------------------------	-----------