

GARANT Master Titan solid carbide finishing cutter HPC, uncoated, \varnothing e8 DC: 12mm



Order data

Order number	203632 12
GTIN	4045197991607
Item class	11Z

Description

Version:

For **finishing operations**.

Special geometry for optimum chip evacuation.

Unequal spacing gives high intrinsic stability and smooth cutting action.

For profile milling as a finishing operation in titanium and titanium alloys.

Advantage:

Suitable for medical technology and approved for foodstuffs.

Technical description

Overall length L	83 mm	
elix angle 40 degrees		
Cutting edge Ø D _C	12 mm	
No. of teeth Z	7	
Feed f_z for side milling in titanium > 850 N/mm ²	0.04 mm	
Shank	DIN 6535 HA to h6	
Tolerance nominal Ø	e8	
Direction of infeed	horizontal	
Flute length L _c	26 mm	
Shank Ø D _s	12 mm	



Corner rounding r _v	0.05 mm	
Series	Master Titan	
Coating	uncoated	
Tool material	Solid carbide	
Standard	Manufacturer's standard	
Туре	N	
Helix angle characteristic	unequal spacing	
Cutting width a_e for milling operation	0.1×D for side milling	
Through-coolant	no	
Machining strategy	HPC	
Colour ring	pink	
Type of product	End / face mill	

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu plastics	suitable only under restricted conditions	130 m/min	N
Aluminium (short chipping)	suitable only under restricted conditions	100 m/min	N
Alu > 10% Si	suitable only under restricted conditions	85 m/min	N
Ti > 850 N/mm ²	suitable	60 m/min	S
wet maximum	suitable		

Services

Shank grinding Type HB	129100 HB
------------------------	-----------