



## Jobber drill HSS-E N, uncoated, Ø DC h8: 12mm



### Order data

Order number	114405 12
GTIN	4045197535542
Item class	12B

### Description

#### Version:

**Profile ground:** this ensures high concentricity and pitch accuracy. Precision ground point. Drill for production use.

With point geometry shape C from size 2 mm

#### Recommendation:

#### Maximum drilling depth:

$$L_2 = L_c - 1.5 \times D_c.$$

### Technical description

Flute length $L_c$	101 mm
Number of cutting edges $Z$	2
Nominal $\varnothing D_c$	12 mm
Feed $f$ in steel $< 750 \text{ N/mm}^2$	0.16 mm/rev.
Tolerance nominal $\varnothing$	h8
Shank $\varnothing D_s$	12 mm
Overall length $L$	151 mm
Standard	DIN 338
recommended maximum drilling depth $L_2$	83 mm
Point angle	135 degrees
Shank	Plain shank
Coating	uncoated

Tool material	HSS E
Type	N
Through-coolant	no
Colour ring	without
Type of product	Jobber drill

### User data

	Suitability	V <sub>c</sub>	ISO code
Steel < 500 N/mm <sup>2</sup>	suitable	35 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	28 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	22 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable	8 m/min	P
Steel < 1400 N/mm <sup>2</sup>	suitable	6 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	8 m/min	M
Oil	suitable		
wet maximum	suitable		