HOLEX

HSS core drill Depth of cut 30 mm, uncoated, ∅ DC: 26mm

Order data

Order number	118790 26
GTIN	4045197514943
Item class	12D

Description

Version:
Suitable for all popular magnetic core drilling machines. Very good cutting properties due to optimised cutting edge geometry. Easy to regrind. With Weldon shank - ∅ **19 mm.**
HSS uncoated – attractively priced alternative.
Application:
On mobile magnetic drilling machines or stationary pillar drilling machines to produce large holes in steel construction. The core drill cuts only a thin material ring. The drilled core is ejected by a spring loaded ejector pin.
Supplied with:
Without ejector pin.
Note:
For the lubrication of core drills, we recommend high performance cutting oil (see No. 084210).

Technical description

Nominal ∅ D_C	26 mm
Shank ∅	19 mm
Cutting depth	30 mm
Coating	uncoated
Tool material	HSS
Standard	Manufacturer's standard
Shank	Weldon shank

Colour ring	without
Type of product	Core drill

User data

	Suitability	V_c	ISO code
Alu plastics	suitable	60 m/min	N
Aluminium (short chipping)	suitable	60 m/min	N
Steel < 500 N/mm²	suitable	15 m/min	P
Steel < 750 N/mm²	suitable	10 m/min	P
INOX < 900 N/mm²	suitable	10 m/min	M
Uni	suitable		
Oil	suitable		
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable only under restricted conditions		