

**Garant**
**GARANT Master TM plain shank thread mill 2×D, TiAlN, UNC: 3/8-16**

**Order data**

Order number	139722 3/8-16
GTIN	4062406057954
Item class	11D

**Description**
**Version:**

Solid carbide thread milling cutters **with irregular cutting edge spacing and an increased number of cutting edges**. Due to the **irregular cutting edge spacing** they achieve very **smooth running** and **long tool life**.

**Newly developed universal geometry** and **high-performance coating** for use across a wide spectrum of materials.

- **Significantly reduced vibration due to irregular cutting edge spacing.**
- **Increased number of cutting edges.**
- **New coating for optimum wear resistance.**
- **Corrected thread profile for avoidance of profile distortions.**

**Application:**

For **UNC unified coarse threads** ASME-B1.1.

**Note:**

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 139722 + 129100 HB**

Form **HE**: order with **No. 139722 + 129100 HE**

Thread type: UNC

Thread type: UNC-LH

No. of teeth Z: 4

Threads per inch: 16

Nominal  $\varnothing D_c$ : 7.5 mm

Flute length  $L_c$ : 19.8 mm

Shank length  $L_s$ : 36 mm

Overall length L: 68 mm

Shank  $\varnothing D_s$ : 8 mm

**Technical description**

Thread type	UNC
Thread type	UNC-LH
Shank $\varnothing D_s$	8 mm
Shank length $L_s$	36 mm
No. of teeth $Z$	4
Thread pitch	1.587 mm
Overall length $L$	68 mm
Threads per inch	16
Thread $\varnothing$	9.53 mm
Number of clamping slots	4
Flute length $L_c$	19.8 mm
Feed $f_z$ in steel $< 750 \text{ N/mm}^2$	0.07 mm
Thread size	3/8-16 UNC
Nominal $\varnothing D_c$	7.5 mm
Series	Master TM
Coating	TiAlN
Flank angle	60°
Tool material	solid carbide
Shank	DIN 6535 HA with h6
Through-coolant	yes
Cutting direction	right-hand
Application for type of drilling	up to 2×D for blind holes
Application for type of drilling	up to 2×D for through holes
Spacing of the cutters	unequal spacing
Shank tolerance	h6
Colour ring	green
Internal/external application	Internal
Type of product	thread milling cutter

## User data

	Suitability	V <sub>c</sub>	ISO code
Alu plastics	Suitable	220 m/min	N
Aluminium (short chipping)	suitable	220 m/min	N
Alu > 10% Si	Suitable	180 m/min	N
Steel < 500 N/mm <sup>2</sup>	Suitable	140 m/min	P
Steel < 750 N/mm <sup>2</sup>	Suitable	130 m/min	P
Steel < 900 N/mm <sup>2</sup>	Suitable	120 m/min	P
Steel < 1100 N/mm <sup>2</sup>	Suitable	90 m/min	P
Steel < 1400 N/mm <sup>2</sup>	Suitable	80 m/min	P
Steel < 50 HRC	suitable only under restricted conditions	45 m/min	H
TOOLOX 33	Suitable	85 m/min	H
TOOLOX 44	Suitable	50 m/min	H
INOX < 900 N/mm <sup>2</sup>	Suitable	82 m/min	M
INOX > 900 N/mm <sup>2</sup>	Suitable	75 m/min	M
Ti > 850 N/mm <sup>2</sup>	Suitable	50 m/min	S
GG(G)	Suitable	120 m/min	K
CuZn	Suitable	200 m/min	N
Uni	Suitable		
wet maximum	Suitable		
wet minimum	Suitable		
Air	Suitable		

## Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE

