

Garant GRIDLINE

Base cabinet with drawer, Roller shutter, 36×14G, Height: 2000mm**Order data**

| | |
|--------------|---------------|
| Order number | 940109 2000 |
| GTIN | 4062406068783 |
| Item class | 9GI |

Description**Version:**

Equipped cabinet in 40×20G, with drawers 36×14G.

Mountings for shelves at 25 mm intervals. Swing doors reinforced on the inside and can be locked by 2-component Haptoprene® push handle using a cylinder lock. **Levelling base** for base cabinets, with 4 individually adjustable feet to compensate for unevenness in the floor. In the base cabinet the push handle is mounted in the upper part of the door; in the top-mounted cabinet it is in the lower part of the door.

Drawers with front height 125 mm.

Supplied with:

Cabinet with shelves and drawers.

Colour:

Body and drawer bodies RAL 7035 light grey **powder-coated**. Roller shutter of anodised aluminium profiles, colour not configurable.

Doors and drawer fronts RAL 7016 anthracite, **powder-coated**.

Note:

For storage shelves and accessories for GridLine cabinets see No. 940501 – 940710 and Group 95. According to the TÜV GS certification, it is essential that all cabinets are secured against tipping over.

Technical description

| | |
|---|--|
| Electronic locking system can be retrofitted | yes |
| Number of shelves | 3 |
| Drawer/pull-out shelf load capacity | 75 kg |
| Number of drawers | 3 |
| Cabinet fronts | Roller shutter |
| Weight | 115 kg |
| ComfortClose | no |
| Usable height | 1845 mm |
| Shelf load capacity / maximum distributed shelf load (on metal) | 100 kg |
| Drawer runner extension (partial/full extension) | 100 % |
| Width | 1000 mm |
| Handle positioning | bottom |
| Height | 2000 mm |
| Depth | 500 mm |
| Depth in G | 20 |
| Drawer usable depth | 350 mm |
| Width in G | 40 |
| Drawer usable depth in G | 14 |
| Drawer usable width in G | 36 |
| Drawer usable width | 900 mm |
| Drawer usable area in G | 36×14 |
| Material thickness | 0.9 mm |
| Cabinet housing internal load capacity | 1000 kg |
| Door opening angle | 250 degrees |
| Height adjustment interval | 25 mm |
| Cylinder lock | modular barrel |
| Colour selection | RAL 9002, 7035, 7005, 7016, 6011, 5018, 5012, 5011, 5005, 3003 |

| | |
|---|----------------------|
| Drawer usable width × usable depth in G | 36×14G |
| Type of cabinet | Base cabinet |
| Type of product | Cabinet with shelves |

Accessories

| | |
|---|------------|
| Drawer for sliding door cabinets,Width 40G Drawer front height 125 mm | 940652 125 |
| Drawer for sliding door cabinets,Width 40G Drawer front height 75 mm | 940652 75 |
| Drawer for sliding door cabinets,Width 40G Drawer front height 150 mm | 940652 150 |
| Drawer for sliding door cabinets,Width 40G Drawer front height 200 mm | 940652 200 |
| Comfort Close drawer closure damping system Load capacity of the drawer 75 kg | 950180 75 |
| Drawer for sliding door cabinets,Width 40G Drawer front height 100 mm | 940652 100 |
| Drawer for sliding door cabinets,Width 40G Drawer front height 300 mm | 940652 300 |