

Garant
Machine tap for synchronised spindles HSS-E-PM IC / Form C, DLC, G: G1/8

Order data

Order number	137346 G1/8
GTIN	4045197705600
Item class	11H

Description
Version:

Sturdy version with right-hand helix and shank to DIN 1835-B. Special geometry for use on machines with **synchronised spindle drives**. The tap is controlled by the synchronising spindle of the machine. With the latest generation of special **DLC coating sp²**. For use with **emulsion** (fat content minimum 8%).

With **internal coolant supply** for maximum tool life.

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Note:

For use on synchronised spindles, the **GARANT** quick-change tapping chuck **No. 338100 – 338121 with minimum length adjustment (MLA)** ensures very high process reliability.

Tool material: HSS E PM

Threads per inch: 28

Thread Ø: 9.73 mm

Overall length L: 90 mm

Shank Ø D_s: 8 mm

Shank square □: 6.2 mm

Tapping hole Ø: 8.8 mm

Technical description

Number of cutting edges Z	3
Thread pitch	0.907 mm
Tapping hole Ø	8.8 mm
Threads per inch	28

Number of clamping slots	3
Thread Ø	9.73 mm
Tool material	HSS E PM
Shank Ø D _s	8 mm
Overall length L	90 mm
Shank square □	6.2 mm
Thread depth	24.33 mm
Thread size	G1/8
Coating	DLC
Thread type	G
Flank angle	55 °
Standard	Manufacturer's standard
Taper lead form	C
Helix angle	40 °
Shank	DIN 1835 B to h6
Through-coolant	yes
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Shank tolerance	h6
Type of threading tool	Machine tap for synchronous machining
Colour ring	yellow
Type of product	Tap

User data

	Suitability	V _c	ISO code
Aluminium	suitable	30 m/min	N
Aluminium (short chipping)	suitable	35 m/min	N

Alu > 10% Si	suitable	20 m/min	N
PMMA acrylic	suitable	25 m/min	N
PA 66 GF30	suitable only under restricted conditions	20 m/min	N
PTFE CF25	suitable	25 m/min	N
Cu	suitable	55 m/min	N
CuZn	suitable	35 m/min	N
wet maximum	suitable		
wet minimum	suitable		
Air	suitable		