Garant

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, ∅ DC h7: 4,76-Xmm

Order data

Order number	123025 4,76-X
GTIN	4062406079871
Item class	11E

Description

Version:
Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.
· **Clear reduction in cutting forces due to special cutter geometry.**
· **Coating for best wear resistance even at high process temperatures.**
· **Polished flutes for good chip clearance.**
A **slim chisel point** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.
Note:
Flute length $L_C = L_2 + 1.5 \times D_C$.
Versions HB and HE supplied at the same price as HA.
Form **HB:** order with **No. 123026**.
Form **HE:** order with **No. 123025 + 129100HE**. Delivery time: 12 working weeks
Minimum order quantity: 3 pcs
Items made to order for a specific customer:
Cancellation only up to a maximum of 3 working days after receipt of order acknowledgement. Items cannot be returned. We reserve the right to over-deliver or under-deliver by ±10% (minimum 1 piece).

Technical description

Overall length L	95 mm
Standard	Manufacturer's standard
Shank ∅ D_s	6 mm

Tolerance nominal ∅	h7
Number of cutting edges Z	2
Flute length L_c	57 mm
∅ range	4.76 - 6.05 mm
Series	Master Steel
Coating	TiAlN
Tool material	Solid carbide
Version	8×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

User data

	Suitability	V_c	ISO code
Steel < 500 N/mm²	suitable	195 m/min	P
Steel < 750 N/mm²	suitable	150 m/min	P
Steel < 900 N/mm²	suitable	135 m/min	P
Steel < 1100 N/mm²	suitable	125 m/min	P
Steel < 1400 N/mm²	suitable	80 m/min	P
INOX < 900 N/mm²	suitable only under restricted conditions	65 m/min	M
GG	suitable	120 m/min	K
GGG	suitable	115 m/min	K
Uni	suitable		
wet maximum	suitable		

wet minimum	suitable